

**023Z5009** **Hermetic filter drier, DCL, Steel**

Inlet connection type: Flare, Outlet connection type: Flare

**PRODUCT DETAILS**

<b>Gross weight</b>	0.812 Kg
<b>Net weight</b>	0.728 Kg
<b>Volume</b>	1.282 Liter
<b>EAN</b>	5702428156028
<b>Acid capacity [g]</b>	3.11 g
<b>Acid capacity [oz]</b>	0.11 oz
<b>Activated alum/Molec sieve [%]</b>	20% / 80%
<b>Approval</b>	UL
<b>Body material</b>	Steel
<b>Braket</b>	No
<b>Brand</b>	ELIMINATOR
<b>Category</b>	Art. 3, par. 3
<b>Connection material</b>	Steel
<b>Core</b>	Solid core
<b>Core Size code</b>	16 cu.in.
<b>Drying Cap[Drops of Water]24°C</b>	R134a: 443
<b>Drying Cap[Drops of Water]52°C</b>	R134a: 405
<b>Flow Capacity KW</b>	R134a: 26.6
<b>Flow Capacity TR</b>	R134a: 7.6
<b>Flow direction indicator</b>	Label printed 1-way arrow
<b>Fluid Group</b>	2
<b>Inlet 1 connection size [in]</b>	1/2 in
<b>Inlet connection size [mm]</b>	12 mm
<b>Inlet connection type</b>	Flare
<b>LiqCap Cond (ARI 710-2009)[SI]</b>	Delta p=0.07bar tliq= 30°C tvap=-15°C
<b>LiqCapCond (ARI 710-2009)[IMP]</b>	DELTA P=1PSI tliq= 86°F tvap=5°F
<b>Lubricants compatibility</b>	Oilfree applications
<b>Max. Working Pressure [bar]</b>	46 bar
<b>Max. Working Pressure [psig]</b>	667 psig
<b>Net volume [foz US]</b>	7.63 Fluid Ounce US
<b>Net volume [l]</b>	0.226 L
<b>Oil free refrigerants</b>	R1234ze(E) R134a R513A R515A

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## Product Detail | Hermetic filter drier, DCL, Steel

## PRODUCT DETAILS

<b>Outlet 1 connection size [in]</b>	1/2 in
<b>Outlet connection size [mm]</b>	12 mm
<b>Outlet connection type</b>	Flare
<b>Packing format</b>	Multi pack
<b>Product accessories</b>	Generic accessories
<b>Product description</b>	Liquid line filter drier
<b>Product group</b>	Filter driers
<b>Product Name Description</b>	Hermetic filter drier
<b>Quantity per packing format</b>	12 pc
<b>REACH Candidate List substances</b>	No
<b>Refrigerants</b>	R1234yf R125 R134a R22/R407C R23 R32 R404A R407A R407F R410A R422B R422D R438A R444B R448A R449A R449B R450A R452A R452B R454B R455A R507A R513A R1234ze(E) R1233zd(E) R407H R454A R454C R463A R515B R516A
<b>Serviceable</b>	No
<b>Shell volume [foz US]</b>	11.97 Fluid Ounce US
<b>Shell volume [l]</b>	0.35 L
<b>Solid core surface [cm<sup>2</sup>]</b>	183 cm <sup>2</sup>
<b>Solid core surface [in<sup>2</sup>]</b>	28.34 in <sup>2</sup>
<b>Solid core volume [cm<sup>3</sup>]</b>	128 cm <sup>3</sup>
<b>Solid core volume [in<sup>3</sup>]</b>	7.84 in <sup>3</sup>
<b>Temperature range [°C] [Max]</b>	70 °C
<b>Temperature range [°C] [Min]</b>	-40 °C
<b>Temperature range [°F] [Max]</b>	160 °F
<b>Temperature range [°F] [Min]</b>	-40 °F
<b>Type</b>	DCL

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



---

**PRODUCT DETAILS**

---

<b>Type designation</b>	DCL 164
<b>UL approval file name</b>	SA6398
<b>UL approved refrigerants</b>	R125 R134a R22 R23 R404A R407A R407C R407F R410A R422B R422D R438A R448A R449A R449B R450A R452A R507A R513A

---

**For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)**