

## 068-2008 🖻

**Orifice for expansion valve, Orifice, R407C; R236fa; R452A; R407A; R134a/R513A; R404A/R507A; R448A; R23; R22/R407C; R449A** Temperature range [°C]: -40 - 10



## **PRODUCT DETAILS**

PRODUCT DETAILS	
Gross weight	0.018 Kg
Net weight	0.013 Kg
Volume	0.017 Liter
EAN	5702422020400
Approval	EAC
	LLC CDC TYSK
Design	SAE flare only
Fluid Group	1
Orifice size	05
Packing format	Multi pack
Parts Program name	T2/TE2
Product accessories	TXV accessories
Product group	Expansion valves
Product Name Description	Orifice for expansion valve
Quantity per packing format	25 pc
Rated cap. cond. Range N [IMP]	tcond=100 °F
	tevap=40 °F
	tliq=98 °F
Rated cap. cond. Range N [SI]	tcond=38 °C
	tevap=4.4 °C
	tliq=37 °C
Rated cap. R134a, Range N [kW]	8.4 kW
Rated cap. R134a, Range N [TR]	2.4 TR
Rated cap. R22, Range B [kW]	7.3 kW
Rated cap. R22, Range B [TR]	2.1 TR
Rated cap. R22, Range N [kW]	16.7 kW
Rated cap. R22, Range N [TR]	4.8 TR
Rated cap. R404A, Range B [kW]	5.9 kW
Rated cap. R404A, Range B [TR]	1.7 TR
Rated cap. R404A, Range N [kW]	13 kW
Rated cap. R404A, Range N [TR]	3.7 TR
Rated cap. R407C, Range N [kW]	16.5 kW
Rated cap. R407C, Range N [TR]	4.7 TR
Rated cap. R507, Range B [kW]	5.9 kW
Rated cap. R507, Range B [TR]	1.7 TR
Rated cap. R507, Range N [kW]	13 kW
Rated cap. R507, Range N [TR]	3.7 TR
Rated cap. R513A, Range N [kW]	6.9 kW
Rated cap. R513A, Range N [TR]	2 TR

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



## **PRODUCT DETAILS**

REACH Candidate List substances	Lead (CAS no. 7439-92-1)	
Refrigerants	R22/R407C	
	R23	
	R236fa	
	R407C	
	R134a/R513A	
	R407A	
	R448A	
	R449A	
	R452A	
	R404A/R507A	
Serviceable	No	
Temperature range [°C] [Max]	10 °C	
Temperature range [°C] [Min]	-40 °C	
Temperature range [°F] [Max]	50 °F	
Temperature range [°F] [Min]	-40 °F	
Туре	Orifice	

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 🗈

**Spare Parts** 



## **068-0003** <sup>IZ</sup> Spare part, T 2; TE 2, Filter

Product Type: Spare part, Used for product: T 2; TE 2, Type designation: Filter, Filter

For more information, please use this link to visit the product page on Danfoss Product Store 🗅

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.