

**067G2701** 

Orifice for expansion valve, Orifice, R407C; R452A; R407A; R134a; R407F; R404A/  
R507A; R513A; R22; R448A; R449A



**PRODUCT DETAILS**

<b>Gross weight</b>	0.281 Kg
<b>Net weight</b>	0.25 Kg
<b>Volume</b>	0.283 Liter
<b>EAN</b>	5702428322225
<b>Approval</b>	EAC LLC CDC TYSK
<b>Balanced port [Yes/No]</b>	Yes
<b>Orifice size</b>	10
<b>Packing format</b>	Multi pack
<b>Parts Program name</b>	TE 55
<b>Product accessories</b>	TXV accessories
<b>Product group</b>	Expansion valves
<b>Product Name Description</b>	Orifice for expansion valve
<b>Quantity per packing format</b>	8 pc
<b>Rated cap. cond. Range N [IMP]</b>	tcond=100 °F tevap=40 °F tliq=98 °F
<b>Rated cap. cond. Range N [SI]</b>	tconc=38 °C tevap=4.4 °C tliq=37 °C
<b>Rated cap. R134a, Range N [kW]</b>	109 kW
<b>Rated cap. R134a, Range N [TR]</b>	31 TR
<b>Rated cap. R22, Range B [kW]</b>	81 kW
<b>Rated cap. R22, Range B [TR]</b>	23.1 TR
<b>Rated cap. R22, Range N [kW]</b>	169 kW
<b>Rated cap. R22, Range N [TR]</b>	48 TR
<b>Rated cap. R404A, Range B [kW]</b>	52.1 kW
<b>Rated cap. R404A, Range B [TR]</b>	14.9 TR
<b>Rated cap. R404A, Range N [kW]</b>	127 kW
<b>Rated cap. R404A, Range N [TR]</b>	36 TR
<b>Rated cap. R407A, Range N [kW]</b>	165 kW
<b>Rated cap. R407A, Range N [TR]</b>	47 TR
<b>Rated cap. R407C, Range N [kW]</b>	162 kW
<b>Rated cap. R407C, Range N [TR]</b>	46 TR
<b>Rated cap. R407F, Range N [kW]</b>	172 kW
<b>Rated cap. R407F, Range N [TR]</b>	49 TR
<b>Rated cap. R507, Range B [kW]</b>	52.1 kW
<b>Rated cap. R507, Range B [TR]</b>	14.9 TR
<b>Rated cap. R507, Range N [kW]</b>	127 kW

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



**PRODUCT DETAILS**

<b>Rated cap. R507, Range N [TR]</b>	36 TR
<b>REACH Candidate List substances</b>	Lead (CAS no. 7439-92-1)
<b>Refrigerants</b>	R134a R22 R407A R407C R407F R448A R449A R452A R513A R404A/R507A
<b>Serviceable</b>	TXV spare parts
<b>Type</b>	Orifice

**For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)**