

**MT32-5VI****Reciprocating compressor, MT32JF5MVE**

Refrigerants: R22, Segment usage: Refrigeration MT, Compressor power supply
[V/Ph/Hz]: 220-240/1/50

PRODUCT DETAILS

Gross weight	26.88 Kg
Net weight	25 Kg
Volume	38.115 Liter
EAN	5702428662338
Approval standard	CCC CE
Auxiliary winding resistance (start winding) for single-phase compressors [Ohm]	4.23
Brand technique	Reciprocating compressor
Capacity control	Fixed speed
Capacity of capacitor A	25 µF
Capacity of capacitor B	135 µF
Capacity of capacitor C	10 µF
Colour	Blue
Compressor power supply [V/Ph/ Hz]	220-240/1/50
Configuration code	Single
Connection type	Rotolock
Cylinder	1
Description	MT032-5
Diameter [mm]	224 mm
Discharge connection height [mm]	68 mm
Discharge connection pipe size [in]	1/2 in
Discharge connection size [in]	1 in
Drawing number	8501021e
Economizer	No
Factory HP [bar]	25 bar
Factory LP [bar]	25 bar
Family	MT
Fitting remark	(shipped with rotolock version only)
Fitting sleeve	ODF
Fitting standard	Rotolock
Gauge port HP	None
Gauge port LP	Schrader
Generation code	M
Glass mounting	Threaded
Glass torque [Nm]	50 N-m
GP LP torque [Nm]	15 N-m

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Reciprocating compressor, MT32JF5MVE

PRODUCT DETAILS

High side max pressure (Ps)	29.4 bar
High Side TS Max	150 °C
High Side TS Min	-35 °C
High Side Volume	0.3 L
High value of nominal voltage at 50Hz [V]	240 V
High value of nominal voltage at 60Hz [V]	0 V
High value of voltage range at 50Hz [V]	264 V
High value of voltage range at 60Hz [V]	0 V
Low side max pressure (Ps)	18.4 bar
Low Side TS Max	50 °C
Low Side TS Min	-35 °C
Low Side Volume	7.5 L
Low value of nominal voltage at 50Hz [V]	220 V
Low value of nominal voltage at 60Hz [V]	0 V
Low value of voltage range at 50Hz [V]	198 V
Low value of voltage range at 60Hz [V]	0 V
LRA	70 A
Main winding resistance for single-phase compressors [Ohm]	0.8
MCC	20 A
Model number	MT32JF5MVE
Motor protection	Internal overload protector
Mounting torque [Nm]	15 N-m
Network power supply [V/Ph/Hz]	220-240/1/50 208-230/1/60
Nominal cooling capacity 60 kBTU/h	33.11 kBTU/h
Nominal cooling capacity at 50Hz	7.3 kW
Nominal cooling capacity at 60Hz	9.7 kW
Number of starts per hour [Max]	12
Oil charge [L]	0.95 L
Oil equalization	3/8" flare SAE
Oil equalization torque [Nm]	30 N-m
Oil reference	160P
Packaging height [mm]	385 mm
Packaging length [mm]	330 mm
Packaging weight [Kg]	27 kg
Packaging width [mm]	295 mm
Packing format	Single pack
Packing quantity	1
Phase	1
Power connections	Spade
Product group	Hermetic compressors
Product Name Description	Reciprocating compressor MT
Refrigerant charge [kg] [Max]	2.5 kg

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Reciprocating compressor, MT32JF5MVE
PRODUCT DETAILS

Refrigerants	R22
Relief valve	None
Rotational speed at 50Hz [rpm]	2900 rpm
Rotational speed at 60Hz [rpm]	0 rpm
Segment usage	Refrigeration MT
Shipped fittings	Suction and discharge solder sleeves, rotolock nuts and gaskets
Shipped instructions	Installation instructions
Shipped mounting	Mounting kit with grommets, bolts, nuts, sleeves and washers
Shipped oil	Initial oil charge
Suction connection height [mm]	263 mm
Suction connection material	-
Suction connection pipe size [in]	5/8 in
Suction connection size [in]	1 1/4 in
Swept volume [cm³]	53.86 cm ³
Technology	Reciprocating
Test dif [bar] [Max]	30 bar
Test HP [bar] [Max]	30 bar
Test LP [bar] [Max]	25 bar
Torque earth [Nm]	3 N-m
Torque power [Nm]	3 N-m
Total height [mm]	333 mm
Type	MT032
Viscosity [cP]	32 cP
Voltage of capacitor A [V]	440 V
Voltage of capacitor B [V]	330 V
Voltage of capacitor C [V]	440 V

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Accessories

8156009 [🔗](#)
Connector, Gasket

Gasket set, 1", 1-1/4", 1-3/4", OSG gaskets black and white


7701026 [🔗](#)
Electrical component, Starting kit

PSC starting kit, 20 µF, 10 µF


8156134 [🔗](#)
Electrical component, Terminal box

Service kit for terminal box 80 x 96 mm, including 1 cover, 1 clamp

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Reciprocating compressor, MT32JF5MVE**Accessories****8153007** [🔗](#)**Connector, Solder sleeve**

Solder sleeve, P06 (1" rotolock, 1/2" ODF)

**8173002** [🔗](#)**Electrical component, Start capacitor**

Start capacitor 330V, 140 µF

**120Z0575** [🔗](#)**Acoustic hood, Reciprocating**

Acoustic hood for one-cylinder compressor

**8153011** [🔗](#)**Connector, Solder sleeve**

Solder sleeve, P09 (1-1/4" rotolock, 5/8" ODF)

**8156131** [🔗](#)**Connector, Gasket**

Gasket, 1-1/4"

**8156001** [🔗](#)**Mounting, Compressor kit**

Mounting kit 1 cyl high

**8156130** [🔗](#)**Connector, Gasket**

Gasket, 1"

Spare Parts**8156145** [🔗](#)**Connector, Gasket**

Gasket for oil sight glass (black chloroprene)

**7701023** [🔗](#)**Electrical component, Starting kit**

CSR starting kit, 25 µF, 10 µF, 140 µF

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Spare Parts

**8173022** [🔗](#)**Electrical component, Relay**Starting relay type RVA-6AMKL/3ARR3J4A4

**120Z0459** [🔗](#)**Heater, PTC heater**PTC heater 27W

**7773106** [🔗](#)**Heater, Crankcase heater**Belt type crankcase heater, 54 W, 230 V

**7703005** [🔗](#)**Connector, Valve set**Valve set, V09 (1-1/4"~5/8"), V06 (1"~1/2")

**7701029** [🔗](#)**Electrical component, Starting kit**CSR starting kit, prewired box, 25 µF, 10 µF, 140 µF

**7754001** [🔗](#)**Lubricant, 160P**Mineral oil, 160P, 2-litre can

**8168031** [🔗](#)**Connector, Rotolock service valve**Rotolock valve, V06 (1" rotolock, 1/2" ODF)

**8168033** [🔗](#)**Connector, Rotolock service valve**Rotolock valve, V09 (1-1/4" rotolock, 5/8" ODF)

**8156019** [🔗](#)**Connector, Sight glass**Oil sight glass with gaskets (black and white)

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.