

**MT64-4VI****Reciprocating compressor, MT64HM4DVE**

Refrigerants: R22, Segment usage: Refrigeration MT, Compressor power supply  
[V/Ph/Hz]: 400/3/50 460/3/60

**PRODUCT DETAILS**

<b>Gross weight</b>	42.2 Kg
<b>Net weight</b>	39.7 Kg
<b>Volume</b>	62.049 Liter
<b>EAN</b>	5702428839563
<b>Approval standard</b>	CCC CE UL
<b>Brand technique</b>	Reciprocating compressor
<b>Capacity control</b>	Fixed speed
<b>Colour</b>	Blue
<b>Compressor power supply [V/Ph/Hz]</b>	400/3/50 460/3/60
<b>Configuration code</b>	Single
<b>Connection type</b>	Rotolock
<b>Cylinder</b>	2
<b>Description</b>	MT064-4
<b>Diameter [mm]</b>	288 mm
<b>Discharge connection height [mm]</b>	74 mm
<b>Discharge connection pipe size [in]</b>	3/4 in
<b>Discharge connection size [in]</b>	1 1/4 in
<b>Drawing number</b>	8502012g
<b>Economizer</b>	No
<b>Factory HP [bar]</b>	25 bar
<b>Factory LP [bar]</b>	25 bar
<b>Family</b>	MT
<b>Fitting remark</b>	(shipped with rotolock version only)
<b>Fitting sleeve</b>	ODF
<b>Fitting standard</b>	Rotolock
<b>Gauge port HP</b>	None
<b>Gauge port LP</b>	Schrader
<b>Generation code</b>	E
<b>Glass mounting</b>	Threaded
<b>Glass torque [Nm]</b>	50 N-m
<b>GP LP torque [Nm]</b>	15 N-m
<b>High side max pressure (Ps)</b>	27.8 bar
<b>High Side TS Max</b>	150 °C
<b>High Side TS Min</b>	-35 °C
<b>High Side Volume</b>	0.6 L

## Product Detail | Reciprocating compressor, MT64HM4DVE

## PRODUCT DETAILS

High value of nominal voltage at 50Hz [V]	400 V
High value of nominal voltage at 60Hz [V]	460 V
High value of voltage range at 50Hz [V]	460 V
High value of voltage range at 60Hz [V]	506 V
Low side max pressure (Ps)	18.4 bar
Low Side TS Max	50 °C
Low Side TS Min	-35 °C
Low Side Volume	16.5 L
Low value of nominal voltage at 50Hz [V]	380 V
Low value of nominal voltage at 60Hz [V]	460 V
Low value of voltage range at 50Hz [V]	340 V
Low value of voltage range at 60Hz [V]	414 V
LRA	64 A
MCC	14 A
Model number	MT64HM4DVE
Motor protection	Internal overload protector
Mounting torque [Nm]	15 N-m
Network power supply [V/Ph/Hz]	380-415/3/50 460/3/60
Nominal cooling capacity 60 kBTU/h	64.51 kBTU/h
Nominal cooling capacity at 50Hz	14.4 kW
Nominal cooling capacity at 60Hz	18.9 kW
Number of starts per hour [Max]	12
Oil charge [L]	1.8 L
Oil equalization	3/8" flare SAE
Oil equalization torque [Nm]	30 N-m
Oil reference	160P
Packaging height [mm]	455 mm
Packaging length [mm]	395 mm
Packaging weight [Kg]	40 kg
Packaging width [mm]	365 mm
Packing format	Single pack
Packing quantity	1
Phase	3
Power connections	Spade
Product group	Hermetic compressors
Product Name Description	Reciprocating compressor MT
Refrigerant charge [kg] [Max]	5 kg
Refrigerants	R22
Relief valve	30 bar/8 bar
Rotational speed at 50Hz [rpm]	2900 rpm
Rotational speed at 60Hz [rpm]	3500 rpm
Segment usage	Refrigeration MT

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

**Product Detail | Reciprocating compressor, MT64HM4DVE**
**PRODUCT DETAILS**

<b>Shipped fittings</b>	Suction and discharge solder sleeves, rotolock nuts and gaskets
<b>Shipped instructions</b>	Installation instructions
<b>Shipped mounting</b>	Mounting kit with grommets, bolts, nuts, sleeves and washers
<b>Shipped oil</b>	Initial oil charge
<b>Suction connection height [mm]</b>	265 mm
<b>Suction connection material</b>	-
<b>Suction connection pipe size [in]</b>	7/8 in
<b>Suction connection size [in]</b>	1 3/4 in
<b>Swept volume [cm<sup>3</sup>]</b>	107.71 cm <sup>3</sup>
<b>Technology</b>	Reciprocating
<b>Test dif [bar] [Max]</b>	30 bar
<b>Test HP [bar] [Max]</b>	30 bar
<b>Test LP [bar] [Max]</b>	25 bar
<b>Torque earth [Nm]</b>	3 N-m
<b>Torque power [Nm]</b>	3 N-m
<b>Total height [mm]</b>	413 mm
<b>Type</b>	MT064
<b>Viscosity [cP]</b>	32 cP
<b>Winding resistance for three-phase compressors with identical windings [Ohm]</b>	2.44 Ohm

**For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store** [↗](#)

**Accessories**

**8156009** [↗](#)
**Connector, Gasket**

Gasket set, 1", 1-1/4", 1-3/4", OSG gaskets black and white


**120Z0576** [↗](#)
**Acoustic hood, Reciprocating**

Acoustic hood for two-cylinder compressor


**120Z0763** [↗](#)
**Mounting, Compressor kit**

Mounting kit 2 cylinder


**8156134** [↗](#)
**Electrical component, Terminal box**

Service kit for terminal box 80 x 96 mm, including 1 cover, 1 clamp

**For more information, please use this link to visit the product page on Danfoss Product Store** [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

---

**Accessories**

---

**8156132** [🔗](#)**Connector, Gasket**

Gasket, 1-3/4"

**8153013** [🔗](#)**Connector, Solder sleeve**

Solder sleeve, P07 (1-3/4" rotolock, 7/8" ODF)

**8156131** [🔗](#)**Connector, Gasket**

Gasket, 1-1/4"

**8153008** [🔗](#)**Connector, Solder sleeve**

Solder sleeve, P04 (1-1/4" rotolock, 3/4" ODF)

---

**Spare Parts**

---

**7705006** [🔗](#)**Electrical component, MCI**

Electronic soft start kit, MCI 15 C

**8156145** [🔗](#)**Connector, Gasket**

Gasket for oil sight glass (black chloroprene)

**8168029** [🔗](#)**Connector, Rotolock service valve**

Rotolock valve, V04 (1-1/4" rotolock, 3/4" ODF)

**120Z0459** [🔗](#)**Heater, PTC heater**

PTC heater 27W

**7773117** [🔗](#)**Heater, Belt heater**

Belt type crankcase heater, 65 W, 400 V

---

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

**Product Detail | Reciprocating compressor, MT64HM4DVE****Spare Parts****7773107** [🔗](#)**Heater, Belt heater**

Belt type crankcase heater, 65 W, 230 V

**7703006** [🔗](#)**Connector, Valve set**

Valve set, V07 (1-3/4"~7/8"), V04 (1-1/4"~3/4")

**120Z0466** [🔗](#)**Heater, Belt heater**

Belt type crankcase heater, 65 W, 460 V

**8168032** [🔗](#)**Connector, Rotolock service valve**

Rotolock valve, V07 (1-3/4" rotolock, 7/8" ODF)

**7754001** [🔗](#)**Lubricant, 160P**

Mineral oil, 160P, 2-litre can

**8156019** [🔗](#)**Connector, Sight glass**

Oil sight glass with gaskets (black and white)

**120Z0891** [🔗](#)**Heater, Belt heater**

Belt type crankcase heater, 65 W, 400 V

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.