

**MTZ100-4VI****Reciprocating compressor, MTZ100HS4AVE**

Refrigerants: R404A; R407C; R452A; R407A; R134a; R407F; R513A; R448A; R449A,
Segment usage: Refrigeration MT, Compressor power supply [V/Ph/Hz]: 400/3/50
460/3/60

PRODUCT DETAILS

Gross weight	66.75 Kg
Net weight	63 Kg
Volume	150.48 Liter
EAN	5702428888301
Approval standard	CE UL
Brand technique	Reciprocating compressor
Capacity control	Fixed speed
Colour	Blue
Compressor power supply [V/Ph/Hz]	400/3/50 460/3/60
Configuration code	Single
Connection type	Rotolock
Cylinder	4
Description	MTZ100-4
Diameter [mm]	352 mm
Discharge connection height [mm]	125 mm
Discharge connection pipe size [in]	3/4 in
Discharge connection size [in]	1 1/4 in
Drawing number	8504010f
Economizer	No
Factory HP [bar]	25 bar
Factory LP [bar]	25 bar
Family	MTZ
Fitting remark	(shipped with rotolock version only)
Fitting sleeve	ODF
Fitting standard	Rotolock
Frequency [Hz]	50/60
Gauge port HP	None
Gauge port LP	Schrader
Generation code	No
Glass mounting	Threaded
Glass torque [Nm]	50 N-m
GP LP torque [Nm]	15 N-m
High side max pressure (Ps)	29.4 bar
High Side TS Max	150 °C
High Side TS Min	-35 °C
High Side Volume	1.2 L

Product Detail | Reciprocating compressor, MTZ100HS4AVE

PRODUCT DETAILS

High value of nominal voltage at 50Hz [V]	400 V
High value of nominal voltage at 60Hz [V]	460 V
High value of voltage range at 50Hz [V]	460 V
High value of voltage range at 60Hz [V]	506 V
IP protection class	IP54 (with cable gland)
Low side max pressure (Ps)	22.6 bar
Low Side TS Max	50 °C
Low Side TS Min	-35 °C
Low Side Volume	31 L
Low value of nominal voltage at 50Hz [V]	380 V
Low value of nominal voltage at 60Hz [V]	460 V
Low value of voltage range at 50Hz [V]	340 V
Low value of voltage range at 60Hz [V]	414 V
LRA	90 A
MCC	22 A
Model Number	MTZ100HS4AVE
Motor protection	Internal overload protector
Mounting torque [Nm]	50 N-m
Network power supply [V/Ph/Hz]	380-415/3/50 460/3/60
Nominal cooling capacity at 50Hz	12.3 kW
Nominal cooling capacity at 60Hz	15.5 kW
Number of starts per hour [Max]	12
Oil charge [L]	3.9 L
Oil equalization	3/8" flare SAE
Oil equalization torque [Nm]	30 N-m
Oil reference	175PZ
Packaging height [mm]	720 mm
Packaging length [mm]	570 mm
Packaging weight [Kg]	70 kg
Packaging width [mm]	400 mm
Packing format	Single pack
Packing quantity	1
Phase	3
Power connections	Screw connectors 10-32 UNF x 9.5
Product Group	Hermetic compressors
Product Name Description	MTZ
Refrigerant charge [kg] [Max]	10 kg
Refrigerants	R134a R404A R407A R407C R407F R448A R449A R452A

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Reciprocating compressor, MTZ100HS4AVE

PRODUCT DETAILS

	R513A
Relief valve	30 bar/8 bar
Rotational speed at 50Hz [rpm]	2900 rpm
Rotational speed at 60Hz [rpm]	3500 rpm
Segment usage	Refrigeration MT
Shipped fittings	Suction and discharge solder sleeves, rotolock nuts and gaskets
Shipped instructions	Installation instructions
Shipped mounting	Mounting kit with grommets, bolts, nuts, sleeves and washers
Shipped oil	Initial oil charge
Suction connection height [mm]	233 mm
Suction connection material	-
Suction connection pipe size [in]	1 1/8 in
Suction connection size [in]	1 3/4 in
Swept volume [cm ³]	171.26 cm ³
Technology	Reciprocating
Test dif [bar] [Max]	30 bar
Test HP [bar] [Max]	30 bar
Test LP [bar] [Max]	25 bar
Torque earth [Nm]	3 N-m
Torque power [Nm]	3 N-m
Total height [mm]	519 mm
Type	MTZ100
Winding resistance for three- phase compressors with identical windings [Ohm]	2.12 Ohm

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Accessories



8173230 [🔗](#)

Electrical component, T block

T block connector 52 x 57 mm



120Z0577 [🔗](#)

Acoustic hood, Reciprocating

Acoustic hood for four-cylinder compressor



120Z0639 [🔗](#)

Lubricant, 175PZ

POE lubricant, 175PZ, 2.5L CAN

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**8153008** [↗](#)**Connector, Solder Sleeve**

Solder sleeve, P04 (1-1/4" rotolock, 3/4" ODF)

**8156132** [↗](#)**Connector, GASKET**

Gasket, 1-3/4"

**8156007** [↗](#)**Mounting, Compressor kit**

Mounting kit for four-cylinder compressor and MS, including 4 grommets, 4 bolts

**8156135** [↗](#)**Electrical component, Terminal box**

Service kit for terminal box 96 x 115 mm, including 1 cover, 1 clamp

**8156009** [↗](#)**Connector, GASKET**

Gasket set, 1", 1-1/4", 1-3/4", OSG gaskets black and white

**8156131** [↗](#)**Connector, GASKET**

Gasket, 1-1/4"

**120Z0638** [↗](#)**Lubricant, 175PZ**

POE lubricant, 175PZ, 1-litre can

**7750009** [↗](#)**Electrical component, Discharge thermostat kit**

Discharge thermostat kit

**8153004** [↗](#)**Connector, Solder Sleeve**

Solder sleeve, P02 (1-3/4" rotolock, 1-1/8" ODF)

For more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Spare Parts

**7705007** [🔗](#)**Electrical component, MCI**

Electronic soft start kit, MCI 25 C

**8168028** [🔗](#)**Connector, Rotolock service valve**

Rotolock valve, V02 (1-3/4" rotolock, 1-1/8" ODF)

**7773108** [🔗](#)**Heater, Belt heater**

Belt type crankcase heater, 75 W, 230 V, CE mark, UL

**8156019** [🔗](#)**Connector, Sight glass**

Oil sight glass with gaskets (black and white)

**8168029** [🔗](#)**Connector, Rotolock service valve**

Rotolock valve, V04 (1-1/4" rotolock, 3/4" ODF)

**120Z0459** [🔗](#)**Heater, PTC heater**

PTC heater 27W, CE mark, UL

**7773118** [🔗](#)**Heater, Belt heater**

Belt type crankcase heater, 75 W, 400 V, CE mark, UL

**120Z0464** [🔗](#)**Heater, Belt heater**

Belt type crankcase heater, 75 W, 460 V, CE mark, UL

**7703009** [🔗](#)**Connector, Valve set**

Valve set, V02 (1-3/4"~1-1/8"), V04 (1-1/4"~3/4")

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Spare Parts



8156145 [🔗](#)

Connector, GASKET

Gasket for oil sight glass (black chloroprene)

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.