



MTZ125-4VI ≥

Reciprocating compressor, MTZ125HU4VE

Refrigerants: R404A; R407C; R452A; R407A; R134a; R407F; R513A; R448A; R449A, Segment usage: Refrigeration MT, Compressor power supply [V/Ph/Hz]: 400/3/50 460/3/60

PRODUCT DETAILS

Gross weight	70.75 Kg
Net weight	67 Kg
Volume	150.48 Liter
EAN	5702428980593
Approval standard	CE
	UL
Brand technique	Reciprocating compressor
Capacity control	Fixed speed
Colour	Blue
Compressor power supply [V/Ph/	400/3/50 460/3/60
Hz]	
Configuration code	Single
Connection type	Rotolock
Cylinder	4
Description	MTZ125-4
Diameter [mm]	352 mm
Discharge connection height [mm]	125 mm
Discharge connection pipe size [in]	3/4 in
Discharge connection size [in]	1 1/4 in
Drawing number	8504010f
Economizer	No
Factory HP [bar]	25 bar
Factory LP [bar]	25 bar
Family	MTZ
Fitting remark	(shipped with rotolock version only)
Fitting sleeve	ODF
Fitting standard	Rotolock
Frequency [Hz]	50/60
Gauge port HP	None
Gauge port LP	Schrader
Generation code	No
Glass mounting	Threaded
Glass torque [Nm]	50 N-m
GP LP torque [Nm]	15 N-m
High side max pressure (Ps)	29.4 bar
High Side TS Max	150 ℃
High Side TS Min	-35 °C
High Side Volume	1.2 L
	· · · · · · · · · · · · · · · · · · ·



PRODUCT DETAILS	
High value of nominal voltage at	400 V
50Hz [V]	
High value of nominal voltage at	460 V
60Hz [V]	
High value of voltage range at 50Hz	460 V
[V]	
High value of voltage range at 60Hz	506 V
[V]	
IP protection class	IP54 (with cable gland)
Low side max pressure (Ps)	22.6 bar
Low Side TS Max	50 ℃
Low Side TS Min	-35 °C
Low Side Volume	31 L
Low value of nominal voltage at	380 V
50Hz [V]	
Low value of nominal voltage at	460 V
60Hz [V]	
Low value of voltage range at 50Hz	340 V
[V]	
Low value of voltage range at 60Hz	414 V
[V]	
LRA	105 A
MCC	27 A
Model Number	MTZ125HU4VE
Motor protection	Internal overload protector
Mounting torque [Nm]	50 N-m
Network power supply [V/Ph/Hz]	380-415/3/50 460/3/60
Nominal cooling capacity at 50Hz	15.7 kW
Nominal cooling capacity at 60Hz	20 kW
Number of starts per hour [Max]	12
Oil charge [L]	3.9 L
Oil equalization	3/8" flare SAE
Oil equalization torque [Nm]	30 N-m
Oil reference	175PZ
Packaging height [mm]	720 mm
Packaging length [mm]	570 mm
Packaging weight [Kg]	71 kg
Packaging width [mm]	400 mm
Packing format	Single pack
Packing quantity	1
Phase	3
Power connections	Screw connectors 10-32 UNF x 9.5
Product Group	Hermetic compressors
Product Name Description	MTZ
Refrigerant charge [kg] [Max]	10 kg
Refrigerants	R134a
	R404A
	R407A
	R407C
	R407F
	R448A
	R449A
	R452A



PRODUCT DETAILS

	R513A	
Relief valve	30 bar/8 bar	
Rotational speed at 50Hz [rpm]	2900 rpm	
Rotational speed at 60Hz [rpm]	3500 rpm	
Segment usage	Refrigeration MT	
Shipped fittings	Suction and discharge solder sleeves,	
	rotolock nuts and gaskets	
Shipped instructions	Installation instructions	
Shipped mounting	Mounting kit with grommets, bolts,	
	nuts, sleeves and washers	
Shipped oil	Initial oil charge	
Suction connection height [mm]	233 mm	
Suction connection material	-	
Suction connection pipe size [in]	1 1/8 in	
Suction connection size [in]	1 3/4 in	
Swept volume [cm3]	215.44 cm ³	
Technology	Reciprocating	
Test dif [bar] [Max]	30 bar	
Test HP [bar] [Max]	30 bar	
Test LP [bar] [Max]	25 bar	
Torque earth [Nm]	3 N-m	
Torque power [Nm]	3 N-m	
Total height [mm]	519 mm	
Туре	MTZ125	
Winding resistance for three-	1.45 Ohm	
phase compressors with identical		
windings [Ohm]		

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 🖸

Accessories



120Z0577 🗷

Acoustic hood, Reciprocating

Acoustic hood for four-cylinder compressor



120Z0639 🗷

Lubricant, 175PZ

POE lubricant, 175PZ,2.5L CAN



8156135 🗷

Electrical component, Terminal box

Service kit for terminal box 96 x 115 mm, including 1 cover, 1 clamp

For more information, please use this link to visit the product page on Danfoss Product Store 🗅



Accessories



120Z0638 🗷

Lubricant, 175PZ

POE lubricant, 175PZ, 1-litre can



7750009 🗷

Electrical component, Discharge thermostat kit

Discharge thermostat kit



8156132 🗷

Connector, GASKET

Gasket, 1-3/4"



8173230 🗈

Electrical component, T block

T block connector 52 x 57 mm



8156009 🗷

Connector, GASKET

Gasket set, 1", 1-1/4", 1-3/4", OSG gaskets black and white



8153004 🗈

Connector, Solder Sleeve

Solder sleeve, P02 (1-3/4" rotolock, 1-1/8" ODF)



8153008 🗷

Connector, Solder Sleeve

Solder sleeve, P04 (1-1/4" rotolock, 3/4" ODF)



8156007 🗷

Mounting, Compressor kit

Mounting kit for four-cylinder compressor and MS, including 4 grommets, 4 bolts



8156131 🗈

Connector, GASKET

Gasket, 1-1/4"



Spare Parts



7705007 🗷

Electrical component, MCIElectronic soft start kit, MCI 25 C



120Z0459 🗈

Heater, PTC heater

PTC heater 27W, CE mark, UL



7703009 🗷

Connector, Valve set

Valve set, V02 (1-3/4"~1-1/8"), V04 (1-1/4"~3/4")



8168029 🗷

Connector, Rotolock service valve

Rotolock valve, V04 (1-1/4" rotolock, 3/4" ODF)



8168028 🗷

Connector, Rotolock service valve

Rotolock valve, V02 (1-3/4" rotolock, 1-1/8" ODF)



8156145 🗷

Connector, GASKET

Gasket for oil sight glass (black chloroprene)



120Z0464 🗷

Heater, Belt heater

Belt type crankcase heater, 75 W, 460 V, CE mark, UL



7773108 🗷

Heater, Belt heater

Belt type crankcase heater, 75 W, 230 V, CE mark, UL



7773118 🗷

Heater, Belt heater

Belt type crankcase heater, 75 W, 400 V, CE mark, UL

For more information, please use this link to visit the product page on Danfoss Product Store 🗷



Spare Parts



8156019 🗷

Connector, Sight glass

Oil sight glass with gaskets (black and white)