

**120F0234****Reciprocating compressor, NTZ096A4LR1B**

Refrigerants: R404A; R452A, Segment usage: Refrigeration LT, Compressor power supply [V]: 400/3/50 460/3/60, Packing format: Single pack

PRODUCT DETAILS

| | |
|--|--|
| Gross weight | 37.67 Kilogram |
| Net weight | 35.18 Kilogram |
| Volume | 61.54 Liter |
| EAN | 5702428521185 |
| Approval | CE UKCA |
| Brand technique | Reciprocating compressor |
| Capacity control | Fixed speed |
| China RoHS compliance | Out of scope |
| Colour | Blue |
| Compressor power supply [V] | 400/3/50 460/3/60 |
| Configuration code | Single |
| Connection type | Rotolock |
| Cylinder | 2 |
| Description | NTZ096-4B |
| Diameter [mm] | 288 mm |
| Discharge connection height [mm] | 74 mm |
| Discharge connection pipe size [in] | 3/4 in |
| Discharge connection size [in] | 1 1/4 in |
| Drawing number | 8502012g |
| Economizer | No |
| EU RoHS compliance | Yes with exemptions |
| EU RoHS exemption clause | 6(a), 6(a)-I, 7(a), 7(c)-I, 8(b), 9(b) |
| Factory HP [bar] | 25 bar |
| Factory LP [bar] | 25 bar |
| Family | NTZ |
| Fitting remark | (shipped with rotolock version only) |
| Fitting sleeve | ODF |
| Fitting standard | Rotolock |
| Frequency [Hz] | 50 |
| Gauge port HP | None |
| Gauge port LP | Schrader |
| Glass mounting | Threaded |
| Glass torque [Nm] | 50 N-m |
| GP LP torque [Nm] | 15 N-m |
| High Side TS Max | 150 °C |
| High Side TS Min | -35 °C |
| High Side Volume | 0.6 L |

Product Detail | Reciprocating compressor, NTZ096A4LR1B

PRODUCT DETAILS

| | |
|---|--|
| High value of nominal voltage at 50Hz [V] | 400 V |
| High value of voltage range at 50Hz [V] | 440 V |
| In scope of WEEE and contain batteries | No |
| IP protection class | IP55 (with cable gland) |
| Low Side TS Max | 50 °C |
| Low Side TS Min | -35 °C |
| Low Side Volume | 16.5 L |
| Low value of nominal voltage at 50Hz [V] | 380 V |
| Low value of voltage range at 50Hz [V] | 340 V |
| LRA | 32 A |
| Max pressure (PS) - high side | 28.5 bar |
| Max pressure (PS) - low side | 22.6 bar |
| MCC | 10.1 A |
| Model number | NTZ096A4LR1B |
| Motor protection | Internal overload protector |
| Mounting torque [Nm] | 15 N-m |
| Network power supply [V/Ph/Hz] | 380-415/3/50 460/3/60 |
| Number of starts per hour [Max] | 12 |
| Oil charge [L] | 1.8 L |
| Oil equalization | 3/8" flare SAE |
| Oil equalization torque [Nm] | 30 N-m |
| Oil reference | 175PZ |
| Packaging height [mm] | 450 mm |
| Packaging length [mm] | 385 mm |
| Packaging width [mm] | 375 mm |
| Packing format | Single pack |
| Packing quantity | 1 |
| Phase | 3 |
| Power connections | Spade |
| Product group | Hermetic compressors |
| Product Name Description | Reciprocating compressor NTZ |
| REACH Candidate List substances | Lead (CAS no. 7439-92-1) |
| Refrigerant charge [kg] [Max] | 5 kg |
| Refrigerants | R404A R452A |
| Rotational speed at 50Hz [rpm] | 2900 rpm |
| SCIP dossier no. | 9b3fb119-9852-486a-92dd-53aa9c96fd3b |
| Segment usage | Refrigeration LT |
| Shipped fittings | Suction and discharge solder sleeves, rotolock nuts and gaskets |
| Shipped instructions | Installation instructions |
| Shipped mounting | Mounting kit with grommets, bolts, nuts, sleeves and washers |
| Shipped oil | Initial oil charge |
| Suction connection height [mm] | 265 mm |
| Suction connection material | - |
| Suction connection pipe size [in] | 7/8 in |

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Reciprocating compressor, NTZ096A4LR1B
PRODUCT DETAILS

| | |
|---|--------------------|
| Suction connection size [in] | 1 3/4 in |
| Swept volume [cm³] | 96 cm ³ |
| Technology | Reciprocating |
| Test dif [bar] [Max] | 30 bar |
| Test HP [bar] [Max] | 30 bar |
| Test LP [bar] [Max] | 25 bar |
| Torque earth [Nm] | 3 N-m |
| Torque power [Nm] | 3 N-m |
| Total height [mm] | 413 mm |
| Type | NTZ096 |
| UK RoHS compliance | Out of scope |
| Winding resistance for three-phase compressors with identical windings [Ohm] | 5.03 Ohm |

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Accessories

120Z0763 [🔗](#)
Mounting, Compressor kit

Mounting kit 2 cylinder


8156134 [🔗](#)
Electrical component, Terminal box

Service kit for terminal box 80 x 96 mm, including 1 cover, 1 clamp


8156009 [🔗](#)
Connector, Gasket

Gasket set, 1", 1-1/4", 1-3/4", OSG gaskets black and white


120Z0576 [🔗](#)
Acoustic hood, Reciprocating

Acoustic hood for two-cylinder compressor


8156131 [🔗](#)
Connector, Gasket

Gasket, 1-1/4"


8156132 [🔗](#)
Connector, Gasket

Gasket, 1-3/4"

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Reciprocating compressor, NTZ096A4LR1B**Accessories****8153013** [🔗](#)**Connector, Solder sleeve**

Solder sleeve, P07 (1-3/4" rotolock, 7/8" ODF)

**8153008** [🔗](#)**Connector, Solder sleeve**

Solder sleeve, P04 (1-1/4" rotolock, 3/4" ODF)

**7750009** [🔗](#)**Electrical component, Discharge thermostat kit**

Discharge thermostat kit

Spare Parts**120Z0466** [🔗](#)**Crankcase heater, Belt heater**

Belt type crankcase heater, 65 W, 460 V

**8156145** [🔗](#)**Connector, Gasket**

Gasket for oil sight glass (black chloroprene)

**8156019** [🔗](#)**Connector, Sight glass**

Oil sight glass with gaskets (black and white)

**7773117** [🔗](#)**Crankcase heater, Belt heater**

Belt type crankcase heater, 65 W, 400 V

**7703006** [🔗](#)**Connector, Valve set**

Valve set, V07 (1-3/4"~7/8"), V04 (1-1/4"~3/4")

**7773107** [🔗](#)**Crankcase heater, Belt heater**

Belt type crankcase heater, 65 W, 230 V

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Spare Parts

**8168029** [🔗](#)**Connector, Rotolock service valve**Rotolock valve, V04 (1-1/4" rotolock, 3/4" ODF)

**120Z0459** [🔗](#)**Crankcase heater, PTC heater**PTC heater 27W

**8168032** [🔗](#)**Connector, Rotolock service valve**Rotolock valve, V07 (1-3/4" rotolock, 7/8" ODF)

**120Z0891** [🔗](#)**Crankcase heater, Belt heater**Belt type crankcase heater, 65 W, 400 V

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.